

SORELL COUNCIL NOTICE OF PROPOSED DEVELOPMENT

Notice is hereby given that an application has been made for planning approval for the following development:

SITE: 223A Old Forcett Road, Forcett

PROPOSED DEVELOPMENT:

DWELLING

The relevant plans and documents can be inspected at the Council Offices at 47 Cole Street, Sorell during normal office hours, or the plans may be viewed on Council's website at www.sorell.tas.gov.au until **Friday 5th April 2024.** Any person may make representation in relation to the proposal/s by letter or electronic mail (sorell.tas.gov.au) addressed to the General Manager. Representations must be received no later than **Friday 5th April 2024.**

APPLICANT: P Pitt

DATE: 14 March 2024

APPLICATION NO: 5.2023.339.1



Part B: Please note that Part B of this form is publicly exhibited.

Full description of Proposal:	Use: Single dwelling			
·	Development: Single stor		ey residential dwelling	
	Large or complex proposals s	hould be	described	in a letter or planning report.
Design and cons	truction cost of proposal:		\$ 750,00	00
Is all, or some th	e work already constructed:		No: 🗹	Yes: □
	2224 014		Dood	
Location of proposed	Street address:	-orceii	Road	
works:	Suburb:		Posto	code:
	Certificate of Title(s) Volum	ie:	1//	Folio:
Current Use of Site Vacant				
Current Owner/s: Name(s) Hannah Spong				
		I		I
Is the Property of Register?	on the Tasmanian Heritage	No: 🗹	Yes: □	If yes, please provide written advice from Heritage Tasmania
Is the proposal t than one stage?	o be carried out in more	No: ☑	Yes: □	If yes, please clearly describe in plans
Have any potentially contaminating uses been undertaken on the site?			Yes: □	If yes, please complete the Additional Information for Non-Residential Use
Is any vegetation proposed to be removed?			Yes: □	If yes, please ensure plans clearly show area to be impacted
Does the proposal involve land administered or owned by either the Crown or Council?			∣ Yes: □	If yes, please complete the Council or Crown land section on page 3
If a new or upgraded vehicular crossing is required from Council to the front boundary please				
	hicular Crossing (and Associa			ation form
https://www.sor	rell.tas.gov.au/services/engir	neering/	<i>'</i>	

Sorell Council

Development Application: Development Application - 223A Old Forcett Road, Forcett.pdf Plans Reference: P1 Date received: 6/12/2023

Part B continued: Please note that Part B of this form is publicly exhibited

Declarations and acknowledgements

- I/we confirm that the application does not contradict any easement, covenant or restriction specified in the Certificate of Title, Schedule of Easements or Part 5 Agreement for the land.
- I/we consent to Council employees or consultants entering the site and have arranged permission and/or access for Council's representatives to enter the land at any time during normal business hours.
- I/we authorise the provision of a copy of any documents relating to this application to any person for the purposes of assessment or public consultation and have permission of the copyright owner for such copies.
- I/we declare that, in accordance with s52(1) of the Land Use Planning and Approvals Act 1993, that I have notified the owner(s) of the intention to make this application.
- I/we declare that the information in this application is true and correct.

Details of how the Council manages personal information and how you can request access or corrections to it is outlined in Council's Privacy Policy available on the Council website.

- I/we acknowledge that the documentation submitted in support of my application will become a public record held by Council and may be reproduced by Council in both electronic and hard copy format in order to facilitate the assessment process, for display purposes during public exhibition, and to fulfil its statutory obligations. I further acknowledge that following determination of my application, Council will store documentation relating to my application in electronic format only.
- Where the General Manager's consent is also required under s.14 of the *Urban Drainage Act 2013*, by making this application I/we also apply for that consent.

Applicant Signature:	Signature: Perri Pitt	. Date:


Crown or General Manager Land Owner Consent

If the land that is the subject of this application is owned or administered by either the Crown or Sorell Council, the consent of the relevant Minister or the Council General Manager whichever is applicable, must be included here. This consent should be completed and signed by either the General Manager, the Minister, or a delegate (as specified in s52 (1D-1G) of the *Land Use Planning and Approvals Act 1993*).

Please note:

- If General Manager consent if required, please first complete the General Manager consent application form available on our website www.sorell.tas.gov.au
- If the application involves Crown land you will also need a letter of consent.
- Any consent is for the purposes of making this application only and is not consent to undertaken work or take any other action with respect to the proposed use or development.

I		being responsible for the
administration of land at		Sorell Council
declare that I have given permission for the making of this application for		Development Application: Development Application - 223A Old Forcett Road, Forcett.pdf Plans Reference: P1 Date received: 6/12/2023
Signature of General Manager, Minister or Delegate:	Signature:	Date:





DISPERSION ASSESSMENT SOIL AND WATER MANAGEMENT PLAN

223A Old Forcett Rd Forcett

February 2024



Development Application: Response to Request for Information - 223A Old Forcett Road, Dodges Ferry.pdf Plans Reference: P2 Date received: 7/03/2024

Site Information

Client: Hannah Spong

Address: 223A Old Forcett Rd, Forcett (CT 182177/2)

Site Area: Approximately 1 ha

Date of inspection: 14/6/2023

Building type: New house

Services: Tank water and Onsite wastewater

Planning Overlays: Dispersive soil specific area plan

Mapped Geology - Mineral Resources Tasmania 1:50 000 Sorell sheet:

Ts = Tertiary sediments of gravel, sand, silt, clay and regolith

Soil Depth: 0.85 - 1.9+ m

Subsoil Drainage: Moderately-well drained

Downslope surface water: nil

Vegetation: woodland

Rainfall in previous 7 days: Approximately 5 mm

Slope: Approximately 6° to the southeast

Site Assessment and Sample Testing

Site and published geological information were integrated to complete a detailed soil dispersion assessment with reference to the DPIWE dispersive soil technical manual.

Test holes were dug using a Christie Post Driver Soil Sampling Kit, comprising CHPD78 Christie Post Driver with Soil Sampling Tube (50 mm OD x 1600/2100 mm).

• Four test hole (TH) cores:

TH1 with no refusal above 2.0 m
 TH3 with refusal at 0.9 m

o TH2 with refusal at 1 m o TH4 with refusal at 0.85 m

• Two Dynamic Cone Penetrometer (DCP) tests:

o DCP1 with refusal at 0.8 m o DCP2 with refusal at 1.0 m

• Emerson Dispersion test on subsoils and linear shrinkage tests on all likely founding layers.

SOIL PROFILES – Test Hole 1



Depth (m)	Horizon	Description and field texture grade	USCS
			Class
0 - 0.7	FILL	Mixed, uncontrolled, majority, sandy	N/A
		topsoil Fill	
0.7 - 1.0	A1	Very dark greyish brown (10YR 2/2)	SP
		Grading to Grey (10YR 5/1), Sand, poorly	
		graded, dry loose consistency	
1.0 - 1.2	A2	Grey (7.5YR 6/1), Fine Sand, poorly	SP
		graded grain, dry dense consistency,	
		abundant gravels, slightly dilatant	
1.2 – 1.3	A3 _h	Dark greyish brown (10YR 4/2), Sticky	OL
		Silty Clay Loam, strong platy structure,	
		dry firm consistency	
1.3 – 1.6	A3 _s	Mixed brownish yellow (10YR 6/8) and	МН
		brown (7.5YR 4/1), Gritty Clay Loam,	
		strong fine angular blocky structure, dry	
		hard consistency, abundant iron stone	
		nodules	
1.6 – 1.9	B2	Light grey (10YR 7/1), Sandy Light Clay,	CL
		with common coarse red and yellow	
		mottles, slightly moist stiff consistency,	
		no refusal	_

SOIL PROFILES – Test Hole 2



Depth (m)	Horizon	Description and field texture grade	USCS Class
0-0.4	A1/A2	Black (10YR 2/1) grading to very dark grey (10YR 3/1), Sand , single grain, dry loose consistency, few roots	SP
0.4 – 0.5	A3 _h	Dark greyish brown (10YR 4/2), Sticky Silty Clay Loam , strong platy structure, dry firm consistency	OL
0.5 – 0.9	B2	Light grey (10YR 7/1), Sandy Light Clay, moderate medium angular blocky structure, slightly moist stiff consistency (0.6 - 0.8 m: weathered sandstone boulder)	CL
0.9 – 1.0	C _w	Red (2.5YR 4/8) and brownish yellow (10YR 6/8), Gritty Sandy Light Clay , strong platy structure, dry stiff consistency, refusal on weathered sandstone bedrock.	CL

SOIL PROFILES – SOIL PROFILES - Test Hole 3

Depth (m)	Horizon	Description and field texture grade	USCS Class
0 – 0.3	A1/A2	Black (10YR 2/1) grading to grey (10YR 5/1), Sand , poorly graded, dry loose consistency, few roots, <u>slightly dilatant</u>	SP
0.3 – 0.5	A3	Pale brown (10YR 6/3), Sand , poorly graded, dry dense consistency.	SP
0.5 – 0.75	B2	Pale brown (10YR 6/3) with fine yellow mottles, Sandy Medium Clay , Strong medium angular blocky structure, dry stiff consistency, sand down cracks.	CL
0.75 – 0.9	Cw	Red (2.5YR 4/8) and brownish yellow (10YR 6/8), Sandy Gritty Light Clay , strong platy structure, dry stiff consistency, refusal on weathered sandstone bedrock.	CL

SOIL PROFILES - Test Hole 4



Depth (m)	Horizon	Description and field texture grade	Soil Cat.
0 - 0.15	A1	Bands of black (10YR 2/1) and very dark grey (10YR 3/1), Sand , single grain, dry loose consistency, disturbed in top 0.2 m, few roots, few fine gravels	SP
0.15 – 0.2	A2	Grey (10YR 5/1), Sand , single grain, dry dense consistency, abundant fine angular silcrete gravels, slightly dilatant	SP
0.2 – 0.35	A3	Grey (7.5YR 6/1), Fine Sand , single grain, dry dense consistency, abundant gravels, slightly dilatant	SP
0.35 - 0.7	B2	Yellowish brown (10YR 5/4), Sandy Light Clay, strong medium platy structure breaking to strong fine angular blocky structure, dry firm friable consistency, few roots	CL
0.7 – 0.85	Cw	Red (2.5YR 4/8) and brownish yellow (10YR 6/8), Sandy Gritty Light Clay , strong platy structure, dry stiff consistency, refusal on weathered sandstone bedrock.	CL

Site and Soil Comments

The natural soil profiles are formed from windblown sands over clayey colluvium derived from Triassic sandstone and upslope Tertiary silica stone. Most of the site is uniformly shallow, with refusal on weathered sandstone bedrock occurring at approximately 0.8 to 1.0 m at THs 2-4 and both DCPs. TH1 at the proposed out-building had approximately 0.7 m of sandy fill above the natural soil profile. Field textures of the soil profiles are dominantly loose sands over sandy light and medium clays. The clays are moderately reactive and moderately to strongly structured. Lab testing revealed subsoil clays with slight and moderate dispersion characteristics, with severity increasing with depth and proximity to the weathered sandstone bedrock.

Potential for dispersive soils

Triassic sediments are known to produce soils with an excess of sodium on the soil exchange complex (clays), which can cause soil dispersion. Under some circumstances, the presence of dispersive soils can also lead to significant erosion, in particular, tunnel and/or gully erosion.

The dispersive soil assessment mainly considers the proposed construction area, including lab testing of all clayey horizons. At the time of the visit, minor site modifications had already occurred, namely, land clearing and minor earthworks (e.g., installation of fence posts, underground powerline to box, etc.). These activities had left piles of worked-up subsoil at the surface, exposed to rainwater. This subsoil displays evidence of dispersive soil phenomena including "melted" soil aggregates, setting and sealing the soil surface, pictured below.




A wider field survey of the surrounding area, found further evidence of dispersive clays. This is most clear in the nearby earth drain and driveway culvert. Shallow rill erosion is occurring in the base of the earth drain, where not armoured/vegetated – pictured below.



The culvert under the property driveway and small section of drain with riprap have silted up with sandy sediments – see image below. Sandy sediment fans typically occur downslope of eroded dispersive sandy clays.





Above: evidence of dispersive weathered Triassic sandstone (the bedrock at the site) found at the site in a near-by road cutting.

Dispersion Testing

The subsoil was tested for dispersion using the Emerson Dispersion method. Photos are shown in Appendix 1. Testing resulted in Emerson Class 2(2), indicating a moderate dispersive characteristic. The clay fines are moderately spontaneously dispersive, meaning exposure to rainfall will likely lead to clay dispersion.

TH#	Depth (m)	Visual sign	Emerson Class
1	1.3 – 1.6	No slaking and no dispersion	8
1	1.6 – 1.9 Some dispersion (Slight milkiness immediately adjacent to aggregate)		2(1)
2	0.75 – 0.9	Some dispersion (obvious milkiness < 50% of aggregate affected)	2(2)
3	0.5 – 0.75	Some dispersion (obvious milkiness < 50% of aggregate affected)	2(2)
3	0.9 – 1.0	Some dispersion (obvious milkiness < 50% of aggregate affected)	2(2)
4	0.35 – 0.6	Some dispersion (Slight milkiness immediately adjacent to aggregate)	2(1)

SOR-S1.7.1 Development on dispersive soils

Objective:

That buildings and works with the potential to disturb dispersive soil are appropriately located or managed:

- (a) to minimise the potential to cause erosion; and
- (b) to reduce risk to property and the environment to an acceptable level.

Acceptable Solutions A1	Comments
Buildings and works must be for:	All stormwater infrastructure
	(downpipes and cut-off drains)
(a) works not involving the release of concentrated	must be directed to the council
water or the disturbance of soils;	stormwater system ASAP
(b) additions or alterations to an existing building, or	during construction
the construction of a non-habitable building,	
provided the development area is not more than	
100m2; or	
(c) forestry operations in accordance with a certified	
Forest Practices Plan.	

Performance Criteria P1	Comments
Buildings and works must be designed, sited and	Site management to minimise
constructed to minimise the risks associated with	exposure of clay subsoils. Use
dispersive soil to property and the environment, having regard to:	of regular gypsum applications to exposed materials and topsoiling and re-vegetation of
(a) the dispersive potential of soils in the vicinity of	all exposed subsoils after
proposed buildings, driveways, services and the development area generally;	construction completion.
(b) the potential of the development to affect or be	Exposed subsoils treated with
affected by erosion, including gully and tunnel erosion;	gypsum at a rate of 1.0 kg/m ² .
(c) the dispersive potential of soils in the vicinity of water drainage lines, infiltration areas and trenches, water storages, ponds, dams and disposal areas;	The level of risk is considered low if the subsoil management program outlined in this report
(d) the level of risk and potential consequences for property and the environment from potential erosion, including gully and tunnel erosion;	is followed.
(e) management measures that would reduce risk to an acceptable level; and	
(f) the advice contained in a dispersive soil	
management plan.	

Soil & Water Management Plan

Detail of works:

At the time of the visit, the site had already been disturbed through vegetation clearing, minor landscaping, and installation of power services.

Site Management recommendations:

- 1. Plan construction to avoid exposing dispersive clay subsoils wherever possible.
- 2. Plan construction activities to minimise subsoil excavation and vegetation stripping.
- 3. Monitor any exposed subsoils for clay dispersion (milky, cloudy water) after rain and, if noted, immediately cover with gypsum 1 kg/m² and re-topsoil and re-vegetate.
- 4. Identify areas for stockpiling of excavated soil material or off-site destination.
- 5. Minimize the length of steep slopes.
- 6. Limit the time bare soil surfaces are exposed to wind and rain the sandy topsoils, while permeable, are prone to wind and water erosion.
- 7. Intercept and safely divert upslope water (run-on) away from the construction area and exposed subsoils.
- 8. Apply mulch or gravel fines to disturbed areas that will be uncovered for more than 1-2 weeks.
- 9. Install permanent storm water drainage measures as part of the first phase of construction e.g. appropriate culverts.
- 10. Ensure runoff from hard areas is discharged to the council stormwater system to avoid erosion of the sandy dispersive soil.
- 11. Connect guttering and pipe work to the stormwater system as soon as possible after roof construction.
- 12. Maintain existing vegetation cover that may act as sediment traps, e.g., on slopes.
- 13. Install sediment traps as close as possible to sediment sources (i.e., house site, soil stockpiles and vehicle wash-down areas)

Maintenance recommendations:

- 1. Display a copy of the SWMP on site and inform all contractors of the content.
- 2. Check and clean sediment fences weekly to avoid overloading and failure.
- 3. Check condition of staked straw bale sediment traps weekly and restock with straw bales as required.
- 4. Monitor soil and building material stockpile levels and move sediment fences to accommodate changes.
- 5. Check all stormwater drains weekly and remove any material which is causing blockages.
- 6. Ensure all erosion control measures are in place until vegetation is re-established on site.

It is recommended that during construction, Doyle Soil Consulting and/or the design engineer be notified of any major variation to the foundation conditions as predicted in this report.

Conclusions

risk associated with dispersive soils on the site. Our testing found the subsoils at the site to be moderately spontaneously dispersive. A wider survey of the surrounding area found rill erosion due to soil dispersion in exposed subsoils in earth drains, as well as 'melting' of worked-up subsoils exposed to rainwater. The severity of the observed erosion is in keeping with our test results – i.e., mild - but is more pronounced in re-worked local materials.

As such, efforts should be made to cover all exposed subsoils on cut/fill batters with topsoil and seeded with well-suited grass species to exposure avoid rainwater and surface water flows from causing erosion of the sandy clays.

Our site investigations revealed moderately shallow clay subsoils. It is not recommended that these layers be utilised for cut and fill. If they were to be utilised as fill, then treatment with gypsum at a rate of 1.0 kg/m^2 and <u>controlled compaction</u> is required.

Multiple general site management recommendations have been made in this report and a summary of the recommendations can be found in the soil and water management plan (SWMP) for the site in. Further information can also be found in the publication "Dispersive soils and their management – Technical manual" (DPIWE Tas 2009).

Rowan Mason

B.Agr.Sc.(Hons).

Soil Scientist


Dr Richard Doyle

 $\hbox{B.Sc.(Hons), M.Sc.(Geol), Ph.D. (Soil Sci.), CPSS}$


(Certified Prof Soil Scientist)

Geologist and Soil Scientist


APPENDIX 1 – Dispersion Test Results



Doyle Soil Consulting: Site and Dispersion Assessment – 223A Old Forcett Rd, Forcett



TH#	Depth (m)	Visual sign	Emerson Class
1	1.3 – 1.6	No slaking and no dispersion	8
1	1.6 – 1.9 Some dispersion (Slight milkiness immediately adjacent to aggregate)		2(1)
2	0.75 – 0.9	Some dispersion (obvious milkiness < 50% of aggregate affected)	2(2)
3	0.5 – 0.75	Some dispersion (obvious milkiness < 50% of aggregate affected)	2(2)
3	0.9 – 1.0	Some dispersion (obvious milkiness < 50% of aggregate affected)	2(2)
4	0.35 – 0.6	Some dispersion (Slight milkiness immediately adjacent to aggregate)	2(1)





223A Old Forcett Rd, Forcett

SOIL EROSION & WATER MANAGEMENT:

Downpipes to be connected to stormwater disposal as soon as roof is installed.

It is not recommended that the local clay subsoils be utilised for cut and fill. If they were to be utilised as fill, <u>treatment</u> with gypsum at a rate of 1.0 kg/m² and controlled compaction is required.

Ag drains where shown are to be installed prior to footing excavation. Ag drains are to be 100ø, 650 deep with filter sock u.n.o.

All excavated material and wash-down areas to be placed up slope of ag drain or a temporary sediment control fence. Excavated materials to be removed when building works are complete.

Construction vehicles to be parked on the street or driveway once constructed to prevent transferring debris onto street.

Minimise duration and physical extent of unprotected disturbed soil surfaces.

Reinstate topsoil and plant vegetation to minimise soil loss as soon as works in the immediate area are complete.

Dr Richard Doyle Geologist and Soil Scientist

4/3/2024

20

Rowan Mason

13/02/24

Prepared by

lication - 223A Old Forcett Road, rcett.pdf ins Reference: P1 te received: 6/12/2023

SITE INFORMATION

182177/2 LAND TITLE REFERENCE WIND CLASSIFICATION N2 SOIL CLASSIFICATION S

WIND AND SOIL CLASSIFICATION BY DOYLE SOIL CONSULTING, "SITE AND SOIL EVALUATION REPORT FOUNDATION AND WIND LOADING ASSESSMENT", 223A OLD FORCETT ROAD, FORCETT, JUNE 2023, CERT 1349

CLIMATE ZONE BUSHFIRE ATTACK LEVEL TBC

PROPERTY LOCATED WITHIN "BUSHFIRE-PRONE AREAS" LAYER UNDER TASMANIAN PLANNING SCHEME OVERLAY (LISTmap) AS OF 11/05/2023

ALPINE AREA CORROSION ENVIRONMENT LOW OTHER HAZARDS NIL KNOWN

PLANNING & ZONING INFORMATION

ZONING: 11.0 RURAL LIVING ZONE A

TASMANIAN PLANNING SCHEME - SORELL

OVERLAYS:

- BUSHFIRE-PRONE AREAS
- AIRPORT OBSTABLE LIMITATION AREA

SITE AREAS

LAND AREA 1.007ha SITE COVERAGE AREA 283.1m² SITE COVERAGE PERCENTAGE 2.8%

DATE REVISION/ISSUE 02/12/2023 CLIENT REVIEW DRAWING LIS SITE PLAN PART SITE PLAN FLOOR PLAN 23-010 A01P 23-010 A02 05/12/2023 DEVELOP APP ELEVATIONS 1 OF 2 23-010 A03 ELEVATIONS 2 OF 2 3D VIEWS CUT & FILL, SWMP 23-010 A04 23-010 C01



PO Box 2030 Howrah TAS 7018

www.catalystdesignanddrafting.com.au Building Services Provider Licence Nos

0410 606 900

design@catdd.com.au

619068752 & CC6621

• HORIZONTAL DATUM (NORTH) IS APPROXIMATE TO GDA94

VERTICAL DATUM (HEIGHT) IS APPROXIMATE TO AHD

 BOUNDARIES AND CONTOUR HEIGHTS ARE IN METRES. CONTOURS AND ELEVATION DATA APPROXIMATE ONLY.

• SITE INFORMATION NOT VERIFIED BY LAND SURVEYOR.

DIMENSIONS IN ITALICS ARE ROUNDED TO 100mm.

 BACKGROUND PHOTO IMAGES ARE FOR CONTEXT ONLY AND ARE NOT NECESSARILY TO SCALE OR PROPORTION.

Checked: PB BUILDING DESIGNERS

HANNAH SPONG

PROPOSED DWELLING

FORCETT, TAS, 7173


223 OLD FORCETT ROAD,

SITE PLAN


DO NOT SCALE DRAWINGS. USE ONLY WRITTEN DIMENSIONS 23-010

Drawing No: A01

619068752 & CC6621




C:\Users\aruth\Catalyst Design & Daffing\Catalyst Design and Draffing -Documents\Projects\Spong 23-010\Drawings\29-010 Spong 181123A.rvt



NORTH WEST ELEVATION

SCALE 1: 100 at A3



SCALE 1:100 at A3

Sorell Council

evelopment Application: Development oplication - 223A Old Forcett Road,

FCL - FINISHED CEILING LEVEL FFL - FINISHED FLOOR LEVEL

FSL - FINISHED SURFACE LEVEL NGL - NATURAL GROUND LEVEL

DATE	REVISION/ISSUE
02/12/2023	CLIENT REVIEW
05/12/2023	DEVELOP APP

DRAWING LIST SITE PLAN 23-010 A01 23-010 A01P 23-010 A02 23-010 A03 SITE PLAN
PART SITE PLAN
FLOOR PLAN
ELEVATIONS 1 OF 2
ELEVATIONS 2 OF 2
3D VIEWS
CUT & FILL, SWMP 23-010 A04 23-010 C01



Catalyst Design & Drafting Pty Ltd ABN 98 546 582 336 PO Box 2030 Howrah TAS 7018 0410 606 900

HANNAH SPONG PROPOSED DWELLING 223 OLD FORCETT ROAD,

Scale: 1	: 100 at
Drawn: Checked:	PP
Checked:	PB


BUILDING DESIGNERS





SOUTH EAST ELEVATION

SCALE 1: 100 at A3



Sorell Council elopment Application: Development cation - 223A Old Forcett Road,

FCL - FINISHED CEILING LEVEL FFL - FINISHED FLOOR LEVEL

FSL - FINISHED SURFACE LEVEL NGL - NATURAL GROUND LEVEL

DATE REVISION/ISSUE 02/12/2023 CLIENT REVIEW 05/12/2023 DEVELOP APP

DRAWING LIST SITE PLAN 23-010 A01 23-010 A01P 23-010 A02 23-010 A03 23-010 A04 SITE PLAN
PART SITE PLAN
FLOOR PLAN
ELEVATIONS 1 OF 2
ELEVATIONS 2 OF 2
3D VIEWS
CUT & FILL, SWMP 23-010 B01 23-010 C01



Catalyst Design & Drafting Pty Ltd ABN 98 546 582 336 PO Box 2030 Howrah TAS 7018 0410 606 900 design@catdd.com.au

HANNAH SPONG PROPOSED DWELLING 223 OLD FORCETT ROAD,

Scale: 1	: 100 at A
Drawn:	PP
Checked:	PB

BUILDING DESIGNERS



Project No: 23-010

ELEVATIONS 2 OF 2

Drawing No: A04



NORTHWEST 3D VIEW

NOT TO SCALE



DATE REVISION/ISSUE 02/12/2023 CLIENT REVIEW 05/12/2023 DEVELOP APP

DRAWING LIST SITE PLAN PART SITE PLAN FLOOR PLAN ELEVATIONS 1 OF 2 ELEVATIONS 2 OF 2 3D VIEWS CUT & FILL, SWMP

23-010 A01 23-010 A01P 23-010 A02 23-010 A03 23-010 A04 23-010 B01 23-010 C01



Catalyst Design & Drafting Pty Ltd ABN 98 546 582 336 PO Box 2030 Howrah TAS 7018 0410 606 900 design@catdd.com.au

HANNAH SPONG PROPOSED DWELLING Scale: NO SCALE Drawn: PP Checked: PB

BUILDING DESIGNERS

DIMENSIONS IN MILLIMETRES UNLESS OTHERWISE NOTED. DO NOT SCALE DRAWINGS. USE ONLY WRITTEN DIMENSIONS. NOT TO SCALE.

3D VIEWS

Project No: 23-010

PLAN

BUILDING DESIGNERS

FORCETT, TAS, 7173

619068752 & CC6621